

SADKA Bench

LSA1



The picture is only illustrative, it may not exactly match the product described.

Product description	Steel weldment. The construction consists of two side rails welded from a bent strip 50 x 10 mm, a seat is reinforced in the middle by another bent. The seat is made up of 3 rectangular (42 x 117 mm) lathes of length 1800 mm, the backrest is made up of 2 rectangular lathes of same dimensions. A seat and backrest are consisted of boards inserted among the parts of the structure and secured with M8 metric screws and nuts.
Material	Construction: steel grade 11 Solid wood: spruce, oak, wood pine ThermoWood® DOWNLOAD PDF SAMPLER >
Surface treatment	Galvanized steel treated with powder coating in colour variations: RAL 7016 (anthracite grey), RAL 9005 (jet black), RAL 9006 (white aluminium), RAL 9007 (grey aluminium), RAL 9003 (white), RAL 3003 (red), RAL 6021 (green), shade of Corten (rusty). Other RAL shades according to RAL sampler on the web. Spruce – two-layer impregnation and lacquer mixed with water with beeswax Oak – treated with impregnation and a glaze with biocidal effect Thermally modified wood pine ThermoWood® – penetration coating for wood with UV protection
Dimensions	1800×666×798 mm
Anchoring	Anchoring is done with four stainless steel threaded rods M10 of length min. 100 mm and four nut cover caps M10 with a chemical anchor into concrete foundations prepared in advance. A detailed drawing is available for download on the website for each particular product.

